

TECHNICAL DATA SHEET

MASTER F2A No. 89201


Sz. 36 - 48



LABELLING ACCORDING TO STANDARD

<p>Standard for firefighting boots DIN EN 15090</p>	<p>Type 2: all kinds of firefighting and rescue activities, where penetration protection and toe protection is needed.</p> <p>Subcategory F2A: Basic shoe for type 2 + antistatic</p>
<p>Additional requirements</p>	<p>SRC Slip resistance: Slip resistant on floors of ceramic tiles with a sodium lauryl sulfate (SLS) solution and on steel floors with glycerol. When it comes to slip resistance as defined by EN ISO 20345, SRC signifies the best possible rating a safety shoe can reach.</p> <p>HI₃ HEAT INSULATED To max. 250 °C for 40 minutes</p> <p>HRO HEAT RESISTANT OUTSOLE Heat resistance against contact heat, also during short-term high temperatures</p>

FORM

<p>Fire-fighting pull-on boot</p> 	<p>Form D - in size 42, the upper height must be at least 28.0 cm.</p>
---	--

AREAS OF APPLICATION

<p>Areas of application</p>	<p>Outdoor areas Suitable for areas with particularly high safety requirements, preferably for fire service operations Areas with severe effects of heat</p>
-----------------------------	--

FEATURES

Ankle padding	Excellent wearing comfort: the ankle-wrapping padding provides for stability and firm grip and prevents pressure marks.
Donning loops	<ul style="list-style-type: none">• Quicker into the boot: Loops make it easier to put the boots on.
High boot without laces or zippers	<ul style="list-style-type: none">• Quick getting in and out
Heel strap	<ul style="list-style-type: none">• Allows the boots to be put on quickly
Seams made of heat-resistant thread	<ul style="list-style-type: none">• Best possible protection against flames, heat and chemicals. Cleaning does not affect the heat resistance.


UPPER MATERIAL

Cowhide leather - fire-resistant	<ul style="list-style-type: none">• Areas of application S2/S3• Natural material• Wear-resistant• Breathable• Water penetration/absorption in accordance with EN ISO 20345 S2
----------------------------------	---


LINING

Breathable fabric lining	<ul style="list-style-type: none">• Climate-regulating• Good ventilation• Skin-friendly• High absorption and emission of moisture
--------------------------	--

TOE PROTECTION CAP

Steel toe cap 	<ul style="list-style-type: none">• Protection against impacts of min. 200 joules and pressure loading of min. 15 kN• Permanent edge coverage for cushioning• Ergonomically shaped• Comfortable toe room• Good coverage of the little toe area
--	--

INLAY SOLE

Full-length inlay sole 	<ul style="list-style-type: none">• The full-length, exchangeable inlay sole provides the highest possible comfort in safety shoes.• The inlay sole is functionally absorbing and releasing moisture and thus provides for a pleasant foot climate.• Antistatic
---	---

INSOLE

Antistatic soft-fleece insole

Antistatic, even if 100 % dry, without using additional means fulfilling a bridge function to the outsole.

- Approximately 50 % lighter than comparable soles made of natural materials
- Flexible and shape-retaining
- Good air permeability
- Excellent wear resistance
- High moisture absorption
- Quick drying (virtually overnight)

PENETRATION RESISTANCE

Steel midsole

Best possible protection from below: The corrosion-resistant midsole made of stainless steel complies with the penetration safety standard EN 12568 and furthermore fulfils the additional requirements for penetration protection in accordance with EN ISO 20344 / 20345. Particularly recommendable when working in areas where there is an increased risk of injuries due to pointed or sharp objects, such as in the construction industry.

OUTSOLE

STEINAU mono-density tread sole with profile



- Excellent slip resistance
- Antistatic

Outsole: Rubber

- Colour: black
- Profile depth: 6.0 mm
- Particularly abrasion-resistant
- Heat-resistant to approx. 200°C, for short periods to 300°C
- Flexible at cold temperatures to approx. -20°C
- Oil and fuel resistant
- Resistant to a large number of chemicals (acids and alkalis)
- Notch-resistant