



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Phantom Non Ferro EP 90.120.0250

Revision date: 31.01.2017

Product code: 44

Page 1 of 6

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Phantom Non Ferro EP 90.120.0250

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Cutting oil

##### 1.3. Details of the supplier of the safety data sheet

Company name: Van Ommen BV  
 Street: Voorste Kerkweg 4  
 Place: NL-7361 ET Beekbergen  
 Telephone: 0031 (0)55 5067600  
 Telefax: 0031 (0)55 5067601

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Regulation (EC) No. 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

##### 2.2. Label elements

#### SECTION 3: Composition/information on ingredients

##### 3.2. Mixtures

###### Hazardous components

| CAS No     | Chemical name  | Quantity    |
|------------|--|-------------|
|            | EC No  |             |
|            | Index No   |             |
|            | REACH No   |             |
|            | Classification according to Regulation (EC) No. 1272/2008 [CLP]                  |             |
| 64742-56-9 | Baseoil - unspecified, Distillates (petroleum), solvent-dewaxed light paraffinic | 15 - < 20 % |
|            | 265-159-2  |             |
|            | 01-2119480132-48   |             |
|            | Asp. Tox. 1; H304  |             |
| 8042-47-5  | Weißöle nach dab   | 15 - < 20 % |
|            | 232-455-8  |             |
|            | 01-2119487078-27   |             |
|            | Asp. Tox. 1; H304  |             |
| 93820-57-6 | Benzolsulfonsäuren, di-C10-18-alkyl Derivate, Calcium-Salze                      | 1 - < 2.5 % |
|            | 298-637-4  |             |
|            | Skin Irrit. 2, Aquatic Chronic 3; H315 H412                                      |             |
| 64742-53-6 | Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic    | 0.1 - < 1 % |
|            | 265-156-6  |             |
|            | 01-2119480375-34   |             |
|            | Asp. Tox. 1; H304  |             |

Full text of H and EUH statements: see section 16.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### General information

Seek medical attention if problems persist. No administration in cases of unconsciousness or cramps.

###### After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

according to Regulation (EC) No 1907/2006

**Phantom Non Ferro EP 90.120.0250**

Revision date: 31.01.2017

Product code: 44

Page 2 of 6

**After contact with skin**

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap.

**After contact with eyes**

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting. In case of swallowing, keep the patient at rest and contact a doctor.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Water fog. Extinguishing powder. Carbon dioxide. Foam.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

In case of fire may be liberated:

Carbon dioxide (CO<sub>2</sub>).

Carbon monoxide

Nitrogen oxides (NO<sub>x</sub>).

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

See protective measures under point 7 and 8.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers).

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Large quantities remove mechanically

Clean contaminated articles and floor according to the environmental legislation.

Clean with detergents. Avoid solvent cleaners.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Avoid oil mist

Use only in well-ventilated areas.

Direct contact with skins avoid.

When using do not eat, drink or smoke.

**Advice on protection against fire and explosion**

Prevent access by unauthorised personnel.

**Further information on handling**

High slip hazard because of leaking or spilled product.

**7.2. Conditions for safe storage, including any incompatibilities**

according to Regulation (EC) No 1907/2006

**Phantom Non Ferro EP 90.120.0250**

Revision date: 31.01.2017

Product code: 44

Page 3 of 6

**Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.  
Recommended storage temperature: 5-40 °C

**Advice on storage compatibility**

Keep away from food, drink and animal feedingstuffs.  
Do not store with strong oxidizing agents.  
Maximum period of storage (time): 3 Jahre / Years / Jaar

**SECTION 8: Exposure controls/personal protection**
**8.1. Control parameters**
**8.2. Exposure controls**
**Protective and hygiene measures**

Use personal protection equipment as per Directive 89/686/EEC.

**Eye/face protection**

Use glasses or face shield if there is a risk of splashing.

**Hand protection**

Protect skin by using skin protective cream. Wear protective gloves if advisable under safety aspects.  
Wash hands before breaks and after work.  
Gloves of appropriate material (i.e. nitrilic rubber, specification: penetration time: level 6, >480 min., thickness 0,9-1 mm; CE-certified acc. EN 374 cat III)

**Skin protection**

Chemical resistant safety shoes. Take off immediately all contaminated clothing.  
Thorough skin-cleansing after handling the product. Set out skin protection guidelines.

**Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

**SECTION 9: Physical and chemical properties**
**9.1. Information on basic physical and chemical properties**

|                 |                |
|-----------------|----------------|
| Physical state: | liquid         |
| Colour:         | light brown    |
| Odour:          | characteristic |

pH-Value:

not applicable

**Test method**
**Changes in the physical state**

|  |                                     |
|--|-------------------------------------|
| Initial boiling point and boiling range: | >280 °C                             |
| Flash point:                             | 165 °C DIN EN 57                    |
| Lower explosion limits:                  | 1 vol. %                            |
| Upper explosion limits:                  | 10 vol. %                           |
| Vapour pressure:<br>(at 20 °C)           | 0,05 hPa                            |
| Density (at 20 °C):                      | 0,89 g/cm <sup>3</sup> EN ISO 12185 |
| Viscosity / kinematic:<br>(at 40 °C)     | 23 mm <sup>2</sup> /s ASTM D 7042   |

**SECTION 10: Stability and reactivity**

according to Regulation (EC) No 1907/2006

**Phantom Non Ferro EP 90.120.0250**

Revision date: 31.01.2017

Product code: 44

Page 4 of 6

**10.4. Conditions to avoid**

Protect against: heat.

**10.5. Incompatible materials**

The following must be prevented: Oxidizing agents, strong. acid.

**10.6. Hazardous decomposition products**

Hazardous decomposition products: none

**SECTION 11: Toxicological information**
**11.1. Information on toxicological effects**
**Acute toxicity**

| CAS No     | Chemical name  |                   |           |          |        |
|------------|--|-------------------|-----------|----------|--------|
|            | Exposure route   | Dose              | Species   | Source   | Method |
| 64742-56-9 | Baseoil - unspecified, Distillates (petroleum), solvent-dewaxed light paraffinic |                   |           |          |        |
|            | oral   | LD50 > 5000 mg/kg | RAT       |          |        |
|            | dermal   | LD50 >5000 mg/kg  | RABBIT    |          |        |
|            | inhalative (4 h) aerosol   | LC50 >5 mg/l      |           |          |        |
| 8042-47-5  | Weißöle nach dab   |                   |           |          |        |
|            | oral   | LD50 >5000 mg/kg  | Ratte     | OECD 401 |        |
|            | dermal   | LD50 >2000 mg/kg  | Kaninchen | OECD 402 |        |
|            | inhalative (4 h) vapour  | LC50 >5000 mg/l   | Ratte     | OECD 403 |        |
| 64742-53-6 | Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic    |                   |           |          |        |
|            | oral   | LD50 >5000 mg/kg  | Rabbit    |          |        |
|            | dermal   | LD50 >5000 mg/kg  | Rabbit    |          |        |
|            | inhalative (4 h) vapour  | LC50 >5 mg/l      | Rat       |          |        |

**Additional information on tests**

No risks worthy of mention. Practical experience.

The statement is derived from the properties of the single components.

The classification was undertaken in accordance with the calculation method governed by the Preparations Directive (1999/45/EC).

**SECTION 12: Ecological information**
**12.1. Toxicity**

| CAS No    | Chemical name       |                 |           |                |          |        |
|-----------|---------------------|-----------------|-----------|----------------|----------|--------|
|           | Aquatic toxicity    | Dose            | [h]   [d] | Species        | Source   | Method |
| 8042-47-5 | Weißöle nach dab    |                 |           |                |          |        |
|           | Acute fish toxicity | LC50 >1000 mg/l | 96 h      | Leuciscus idus | OECD 203 |        |

**12.4. Mobility in soil**

in delivery condition: liquid

according to Regulation (EC) No 1907/2006

**Phantom Non Ferro EP 90.120.0250**

Revision date: 31.01.2017

Product code: 44

Page 5 of 6

**SECTION 13: Disposal considerations**
**13.1. Waste treatment methods**
**Waste disposal number of waste from residues/unused products**

120107 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; mineral-based machining oils free of halogens (except emulsions and solutions); hazardous waste

**SECTION 14: Transport information**
**Land transport (ADR/RID)**
**Other applicable information (land transport)**

Not restricted

**Inland waterways transport (ADN)**
**Other applicable information (inland waterways transport)**

Not restricted

**Marine transport (IMDG)**
**Other applicable information (marine transport)**

Not restricted

**Air transport (ICAO-TI/IATA-DGR)**
**14.1. UN number:**

No dangerous good in sense of these transport regulations.

IATA-packing instructions - Passenger:

Not restricted

**Other applicable information (air transport)**

Not restricted

**SECTION 15: Regulatory information**
**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**
**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: Baseoil - unspecified, Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified, Distillates (petroleum), hydrotreated light naphthenic

2010/75/EU (VOC): &lt;0,1

2004/42/EC (VOC): &lt;0,1

**Additional information**

According to EC directives or the corresponding national regulations the product does not have to be labelled.

**National regulatory information**

Water contaminating class (D): 1 - slightly water contaminating

**SECTION 16: Other information**
**Relevant H and EUH statements (number and full text)**

H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H412 Harmful to aquatic life with long lasting effects.

**Further Information**

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Phantom Non Ferro EP 90.120.0250

Revision date: 31.01.2017

Product code: 44

Page 6 of 6

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*