

# TECHNICAL DATA SHEET

**APACHE white Low O1 No. 92240**


**Sz. 35 - 48**



## LABELLING ACCORDING TO STANDARD

Standard for occupational shoes EN ISO 20347:2022 O1	Basic requirement for O1: <b>A</b> Antistatic shoe - <b>E</b> Energy absorption in the heel - Closed heel area
Additional requirements	<b>FO FUEL RESISTANCE</b> <b>SR SLIP RESISTANCE</b> on ceramic tile with glycerine.


## FORM

Occupational work shoe 	Form A - in size 42, the upper height must not exceed 11.2 cm.
---	--

## AREAS OF APPLICATION

Areas of application	Dry work areas Areas where there is no risk of falling heavy objects
----------------------	---

## FEATURES

Sizes (unisex model)	<ul style="list-style-type: none"> <li>Expanded size range: available in sizes 35 - 48</li> </ul>
Certification in accordance with DGUV rule 112-191	<ul style="list-style-type: none"> <li>Certified for orthopaedic inserts</li> </ul> 
Low weight	<ul style="list-style-type: none"> <li>Use of especially light textile materials</li> <li>Comfortable</li> </ul>
Low weight sole	<ul style="list-style-type: none"> <li>Comfortable</li> </ul>
Padded upper edge	<ul style="list-style-type: none"> <li>Excellent wearing comfort: the padded upper edge protects the Achilles tendon.</li> </ul>

## FEATURES

Padded tongue	<ul style="list-style-type: none"><li>• Excellent wearing comfort: The tongue prevents pressure marks.</li></ul>
Heel loop	<ul style="list-style-type: none"><li>• Quicker into the shoe: The heel loop makes it easier to get inside the shoe</li></ul>
No metal or leather	<ul style="list-style-type: none"><li>• Low weight</li><li>• Suitable for work areas sensitive to metal</li><li>• Does not trigger metal detectors</li><li>• Use around induction loops is possible</li><li>• Suitable for persons allergic to leather</li></ul>


## UPPER MATERIAL

Microfibre	<ul style="list-style-type: none"><li>• Synthetic material</li><li>• Particularly soft</li><li>• Retains its shape</li><li>• Tear-resistant</li><li>• Quick drying</li><li>• Abrasion-resistant and light</li></ul>
Mesh material	<ul style="list-style-type: none"><li>• Areas of application S1</li><li>• Synthetic material</li><li>• Retains its shape</li><li>• Tear-resistant</li><li>• Quick drying</li><li>• Abrasion-resistant and light</li></ul>

## LINING

Breathable fabric lining	<ul style="list-style-type: none"><li>• Climate-regulating</li><li>• Good ventilation</li><li>• Skin-friendly</li><li>• High absorption and emission of moisture</li></ul>
--------------------------	--

## INLAY SOLE

<p>Full-length inlay sole ESD PRO</p> 	<ul style="list-style-type: none"><li>• ESD EQUIPMENT: Protection against electrostatic discharge (ESD). The full-length, exchangeable inlay sole is conductive and designed for the use in ESD safety footwear according to the standards DIN EN ISO 20345 and DIN EN 61340-5-1.</li><li>• Inlay sole with recycled material content</li><li>• The full-length, exchangeable inlay sole provides the highest possible comfort in safety shoes.</li><li>• The inlay sole is functionally absorbing and releasing moisture and thus provides for a pleasant foot climate.</li><li>• The extreme softness of the PU foam absorbs shocks on impact and increases walking comfort.</li><li>• Improvement of the shoe climate thanks to the PU foam's open cell structure. So the foot is always kept comfortably dry.</li></ul>
---	---

## INSOLE

Antistatic soft-fleece insole

Antistatic, even if 100 % dry, without using additional means fulfilling a bridge function to the outsole.

- Approximately 50 % lighter than comparable soles made of natural materials
- Flexible and shape-retaining
- Good air permeability
- Excellent wear resistance
- High moisture absorption
- Quick drying (virtually overnight)

## OUTSOLE

XL EXTRALIGHT® mono-density sole with profile



- Antistatic
- Excellent slip resistance
- ultralight, very flexible sole

Outsole: EVA (Ethylene-Vinyl-Acetate) with rubber inserts

- Abrasion-resistant
- Colour: white
- Profile depth: 6.0 mm
- Oil and fuel resistant
- with rubber inserts for better grip
- Excellent damping qualities
- Low material density, thereby lower weight