

tesa® 4392

Car masking film - masking and protecting of car bodies before filler and paint jobs

tesa® Easy Protect Premium 4392 has been developed for superior paint and filler jobs. The product prevents from inconvenient spotting on the car body after oven - or IR drying at slight residual moisture. The film on the 150m roll at a width of 4m allows easy application by only one person. The print of the film and the easy measuring guide (every 50 cm) facilitate the utilization.

The excellent electrostatic charge secures a better adherence of the film to surface. Outstanding paint and filler adherence enable brilliant results.

Main Application

- Professional lacquering work
- Protection of car body
- Avoids spotting at slight residual moisture

Technical Data

▪ Backing material	PE film	▪ Temperature resistance	115 °C
▪ Thickness of masking coverage	16 µm	▪ Material of masking coverage	HDPE
▪ Tensile strength	6.9 N/cm		

Properties

- | | | | |
|------------------|---------|-------------------|---------|
| ▪ Anti spotting | ● ● ● ● | ▪ Paint anchorage | ● ● ● ● |
| ▪ Easy to remove | yes | | |

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04392>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.