

tesa® 4394

Masking and protecting of car bodies before filler and paint jobs

tesa® Easy Protect Standard 4394 has been developed for superior paint and filler jobs. The film on the 300m roll at a width of 4m allows easy application by only one person.

The clear print of the film and the easy measuring guide (every 50 cm) facilitate the utilization. The excellent electrostatic charge secure a better adherence of the film to surface. Outstanding paint and filler adherence enable brilliant results.

Main Application

- Professional lacquering work
- Protection of car parts
- Avoids spotting at slight residual moisture

Technical Data

▪ Backing material	PE film	▪ Tensile strength	7.6 N/cm
▪ Thickness of masking coverage	10 µm	▪ Temperature resistance	110 °C

Properties

- | | | | |
|------------------|-----|-------------------|------|
| ▪ Easy to remove | yes | ▪ Paint anchorage | ●●●● |
|------------------|-----|-------------------|------|

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=04394>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.