

# TECHNICAL DATA SHEET

**RENZO Mid ESD S3 No. 765841**


**Sz. 36 - 50**



## LABELLING ACCORDING TO STANDARD

|  |  |
|--|--|
| Standard for safety footwear<br>EN ISO 20345:2022 S3 | Basic requirement for S3:<br><b>A</b> Antistatic shoe - <b>E</b> Energy absorption in the heel - <b>FO</b> Fuel resistance - <b>WPA</b> Water penetration and absorption - <b>P</b> Penetration resistance - Closed heel area - Profiled outsole |
| Additional requirements                              | <b>FO FUEL RESISTANCE</b><br><br><b>SR SLIP RESISTANCE</b> on ceramic tile with glycerine.<br><br><b>SC SCUFF CAP</b><br>The overcap manages a certain amount of abrasion.<br><br><b>LG LADDER GRIP</b><br>Heel edge of at least 10 mm           |

## FORM

|  |   |
|--|---|
| Safety laced boot<br> | Form B - in size 42, the upper height must be at least 11.3 cm. |
|--|---|




## AREAS OF APPLICATION

|                      |  |
|----------------------|--|
| Areas of application | Indoors and outdoors<br>Areas where exposure to moisture is expected (S2)<br>Areas where there is a risk of penetration from pointed and sharp objects (S3/S3L/S3S)<br><br>Areas where there is a risk of electrostatic discharge (ESDS/ESD) |
|----------------------|--|

## FEATURES


|               |  |
|---------------|--|
| ESD equipment | Thanks to its excellent discharge capability, the shoe is suitable for work in ESD sensitive or electrostatically protected areas (EPA). The shoes comply to the standard 61340-5-1. |
|---------------|--|



| <b>FEATURES</b>  |  |
|--|--|
| Sizes (unisex model)   | <ul style="list-style-type: none"> <li>Expanded size range: available in sizes 36 - 50</li> </ul>  |
| Certification in accordance with DGUV rule 112-191   | <ul style="list-style-type: none"> <li>Certified for orthopaedic modifications / inserts</li> </ul>   |
| Three widths   | The comfortable three-widths-system offers more volume to forefoot, instep and toes - thus giving every foot the space it needs.   |
| Full, padded bellows tongue  | <ul style="list-style-type: none"> <li>Excellent wearing comfort: The tongue prevents pressure marks and avoids dirt from entering into the shoe.</li> </ul>   |
| Collar padding   | <ul style="list-style-type: none"> <li>Excellent wearing comfort: the ankle-wrapping, softly padded upper edge provides for stability and grip in the shoe.</li> </ul>   |
| Reflective material  | <ul style="list-style-type: none"> <li>Good visibility in the dark</li> </ul>   |
| PU toe protection (polyurethane)   | <ul style="list-style-type: none"> <li>Directly applied tip protection</li> <li>Excellent wear protection in the shoe tip area</li> <li>Protects the upper material in this area against premature wear</li> </ul>   |
| <b>UPPER MATERIAL</b>  |  |
| Cowhide leather  | <ul style="list-style-type: none"> <li>Areas of application S1/S2/S3</li> <li>Natural material</li> <li>Wear-resistant</li> <li>Breathable</li> <li>Water penetration/absorption in accordance with EN ISO 20345 S2</li> </ul>   |
| <b>LINING</b>  |  |
| Breathable fabric lining   | <ul style="list-style-type: none"> <li>Climate-regulating</li> <li>Good ventilation</li> <li>Skin-friendly</li> <li>High absorption and emission of moisture</li> </ul>  |
| Heel pocket lining   | <ul style="list-style-type: none"> <li>The abrasion-resistant microfibre material is particularly sturdy and provides for a pleasant wearing comfort.</li> </ul>   |
| <b>TOE PROTECTION CAP</b>  |  |
| Steel toe cap<br> | <ul style="list-style-type: none"> <li>Protection against impacts of min. 200 joules and pressure loading of min. 15 kN</li> <li>Permanent edge coverage for cushioning</li> <li>Ergonomically shaped</li> <li>Comfortable toe room</li> <li>Good coverage of the little toe area</li> </ul> |

## INLAY SOLE

Full-length inlay sole  
ESD PRO (rec)



- ESD EQUIPMENT: Protection against electrostatic discharge (ESD). The full-length, exchangeable inlay sole is conductive and designed for the use in ESD safety footwear according to the standards DIN EN ISO 20345 and DIN EN 61340-5-1.
- Inlay sole with recycled material content
- The full-length, exchangeable inlay sole provides the highest possible comfort in safety shoes.
- The inlay sole is functionally absorbing and releasing moisture and thus provides for a pleasant foot climate.
- The extreme softness of the PU foam absorbs shocks on impact and increases walking comfort.
- Improvement of the shoe climate thanks to the PU foam's open cell structure. So the foot is always kept comfortably dry.

## INSOLE

ESD soft-fleece insole

ESD equipment: Protection against electrostatic discharge (ESD), and without using additional means fulfilling a bridge function to the outsole.

- Approximately 50 % lighter than comparable soles made of natural materials
- Flexible and shape-retaining
- Good air permeability
- Excellent wear resistance
- High moisture absorption
- Quick drying (virtually overnight)

## PENETRATION RESISTANCE

Steel midsole

Best possible protection from below: The corrosion-resistant midsole made of stainless steel complies with the penetration safety standard EN 12568 and furthermore fulfils the additional requirements for penetration protection in accordance with EN ISO 20344 / 20345. Particularly recommendable when working in areas where there is an increased risk of injuries due to pointed or sharp objects, such as in the construction industry.

## OUTSOLE

SAFETY-GRIP deep-treaded double-density sole with profile



- S-line shaped configuration of the tread blocks, for an ergonomic foot roll
- Excellent slip resistance
- Antistatic

Outsole: PU (polyurethane)

- Colour: black
- Profile depth: 6.0 mm
- Abrasion-resistant
- Heat-resistant to approx. 130°C
- Flexible at cold temperatures to approx. -20°C
- Oil and fuel resistant

Midsole: PU (polyurethane)

- The soft PU core provides a good impact absorption and high wearing comfort