

WHITE GREASE PRO

Technical Data Sheet

Product name: White Grease Pro
Sales code: 32722

Creation date: 8/2016

Version: I

1: General description

Provides long lasting lubrication to all moving parts. Reduces friction and wear. Water resistant. Protects against corrosion. Visible white film. Can be used in a wide temperature range.

2: Features

- Sprays like an oil but sets like a grease, with white colour for easy visual inspection of the film coverage.
- Contains PTFE(*) for extra lubricity.
- Excellent water resistance.
- Provides long lasting lubrication.
- Does not run or drip off.
- Protects metals and alloys.

3: Applications

- Lubrication of mechanical parts
- Handling equipment
- Chains
- Bearings
- Railroad equipment

4: Directions

- Shake well before use
- Shake until the agitator ball moves freely in the can
- Use extension tube for more precise application
- Do not mix with other products
- Do not use on energized equipment
- Use only with adequate ventilation
- A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products



5: Typical product data (without propellant)

• Appearance	:	paste
• Color	:	white
• Odour	:	solvent
• Density	:	0.794 g/cm ³ (@ 20°C)
• Flash Point	:	< 0 °C
• Vapor density	:	3 (@ 20°C)
• Density active product	:	0.95 g/cm ³ (@ 20°C)
• Flash point active product	:	>200 °C (Open Cup)
• 4-ball weld load active product	:	2600N
• 4-ball wear active product	:	0.52 mm ²
• Operating temperature active product	:	-30 --> +120 °C
• NLGI class	:	2

6: Packaging

Aerosol

12x500 ML

7: Remarks

* PTFE or polytetrafluoroethylene is the chemical name for the solid lubricant, also known by Du Pont's trade name Teflon®.

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.