

TECHNICAL DATA SHEET

CLAY ESD F2A No. 89601


Sz. 38 - 50



LABELLING ACCORDING TO STANDARD





| | |
|--|--|
| <p>Standard for fire-fighting boots DIN EN 15090</p> | <p>Type 2: all kinds of fire-fighting and rescue activities, where penetration protection and toe protection is needed.</p> <p>Subcategory F2A: Basic shoe for type 2 + antistatic</p> |
| <p>Additional requirements</p> | <p>SRC Slip resistance: Slip resistant on floors of ceramic tiles with a sodium lauryl sulfate (SLS) solution and on steel floors with glycerol. When it comes to slip resistance as defined by EN ISO 20345, SRC signifies the best possible rating a safety shoe can reach.</p> <p>HI₃ HEAT INSULATED To max. 250 °C for 40 minutes</p> <p>HRO HEAT RESISTANT OUTSOLE Heat resistance against contact heat, also during short-term high temperatures</p> |

FORM

| | |
|---|--|
| <p>Fire-fighting pull-on boot</p>  | <p>Form D - in size 42, the upper height must be at least 28.0 cm.</p> |
|---|--|

AREAS OF APPLICATION

| | |
|-----------------------------|--|
| <p>Areas of application</p> | <p>Outdoor areas Suitable for areas with particularly high safety requirements, preferably for fire service operations Areas with severe effects of heat Areas where there is a risk of electrostatic discharge (ESDS/ESD)</p> |
|-----------------------------|--|

| FEATURES | | |
|--|--|---|
| ESD equipment | Thanks to its excellent discharge capability, the shoe is suitable for work in ESD sensitive or electrostatically protected areas (EPA). The shoes comply to the standard 61340-5-1. |  |
| Sizes (unisex model) | <ul style="list-style-type: none"> Expanded size range: available in sizes 38 - 50 | |
| Certification in accordance with DGUV rule 112-191 | <ul style="list-style-type: none"> Certified for orthopaedic inserts |  |
| Ankle padding | Excellent wearing comfort: the ankle-wrapping padding provides for stability and firm grip and prevents pressure marks. | |
| Reflective material | <ul style="list-style-type: none"> Good visibility in the dark |  |
| Heel loop | <ul style="list-style-type: none"> Quicker into the shoe: The heel loop makes it easier to get inside the shoe | |
| High boot without laces or zippers | <ul style="list-style-type: none"> Quick getting in and out | |
| Heel strap | <ul style="list-style-type: none"> Allows the boots to be put on quickly | |
| Seams made of heat-resistant Nomex® thread | <ul style="list-style-type: none"> Best possible protection against flames, heat and chemicals. Cleaning does not affect the heat resistance. | |
| Abrasion-resistant toe protection | <ul style="list-style-type: none"> Directly applied to the upper in the shoe tip area Excellent wear protection in the shoe tip area Protects the upper in this critical area against premature wear | |
| Winner Plus X Award | The independent jury for the Plus X Award, the Innovation Prize for Technology, Spot, and Lifestyle, grants a total of seven seals of approval to brands that offer products with a competitive edge in terms of quality and innovation. ELTEN has always seen itself as an innovative business at the cutting edge of technology. |  |
| Flex zone | <ul style="list-style-type: none"> soft flex zones for greater flexibility | |
| Integrated name badge | The boot has a badge that can be individually labelled. This prevents any mix-ups. | |
| UPPER MATERIAL | | |
| Cowhide leather - fire-resistant | <ul style="list-style-type: none"> Areas of application S2/S3 Natural material Wear-resistant Breathable Water penetration/absorption in accordance with EN ISO 20345 S2 | |
| LINING | | |
| Breathable fabric lining | <ul style="list-style-type: none"> Climate-regulating Good ventilation Skin-friendly High absorption and emission of moisture | |
| Heel pocket lining | <ul style="list-style-type: none"> The abrasion-resistant microfibre material is particularly sturdy and provides for a pleasant wearing comfort. | |

TOE PROTECTION CAP

Steel toe cap



- Protection against impacts of min. 200 joules and pressure loading of min. 15 kN
- Permanent edge coverage for cushioning
- Ergonomically shaped
- Comfortable toe room
- Good coverage of the little toe area

INLAY SOLE

Full-length inlay sole
FIREFIGHTERS Level 2



- Full inlay sole in three different heights to optimise the fit
- Level 1: Noticeably more comfort for sturdy feet
- Level 2: Provides comfortable cushioning for moderately sturdy feet
- Level 3: Effective shock absorption and increased grip for slim feet
- The inlay sole is functionally absorbing and releasing moisture and thus provides for a pleasant foot climate.
- Improvement of the shoe climate thanks to the PU foam's open cell structure. So the foot is always kept comfortably dry.
- The extreme softness of the PU foam absorbs shocks on impact and increases walking comfort.
- The full-length, exchangeable inlay sole provides the highest possible comfort in safety shoes.

INSOLE

Antistatic soft-fleece
insole

Antistatic, even if 100 % dry, without using additional means fulfilling a bridge function to the outsole.

- Approximately 50 % lighter than comparable soles made of natural materials
- Flexible and shape-retaining
- Good air permeability
- Excellent wear resistance
- High moisture absorption
- Quick drying (virtually overnight)

PENETRATION RESISTANCE

Steel midsole

Best possible protection from below: The corrosion-resistant midsole made of stainless steel complies with the penetration safety standard EN 12568 and furthermore fulfils the additional requirements for penetration protection in accordance with EN ISO 20344 / 20345. Particularly recommendable when working in areas where there is an increased risk of injuries due to pointed or sharp objects, such as in the construction industry.

OUTSOLE

double-density sole with profile



- Excellent slip resistance
- Antistatic

Outsole: Rubber

- Colour: black
- Profile depth: 6.0 mm
- Particularly abrasion-resistant
- Heat-resistant to approx. 200°C, for short periods to 300°C
- Flexible at cold temperatures to approx. -20°C
- Oil and fuel resistant
- Resistant to a large number of chemicals (acids and alkalis)
- Notch-resistant
- Excellent grip on ladders thanks to the straight heel edge

Midsole: PU (polyurethane)

- The soft PU core provides a good impact absorption and high wearing comfort