

tesa® 64286

Strapping tape for basic applications

tesa® 64286 is a tensilized polypropylene strapping tape with a hot melt adhesive system.

tesa® 64286 exhibits a good tensile strength with low elongation at the same time. The product shows a high peel adhesion.

Main Application

- Palettizing
- Reinforcing
- Closing of shipping cartons

Technical Data

| | | | |
|--------------------|------------------|-----------------------|----------|
| ▪ Backing material | MOPP | ▪ Adhesion to steel | 7.5 N/cm |
| ▪ Total thickness | 73 µm | ▪ Elongation at break | 35 % |
| ▪ Type of adhesive | synthetic rubber | ▪ Tensile strength | 175 N/cm |

For latest information on this product please visit <http://l.tesa.com/?ip=64286>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.