

529 Low Vibration Reciprocating Air Saw



Featuring a patented vibration reduction mechanism, lightweight construction, quiet design, and ergonomic rubber grip, the 529 reciprocating air saw increases operator productivity and comfort. It's the perfect tool, cutting everything from plastics to fiberglass to composites to aluminum and sheet metal. You can use the 529 in a variety of applications, including:

- ▶ Muffler and exhaust work
- ▶ Sunroof installations
- ▶ General body shop repair
- ▶ Flat and curved cuts
- ▶ Intricate patterns

Reduced vibration. Increased productivity.

Features and benefits

- Rubber grip offers **improved comfort** during extended use.
- Integrated **vibration reduction** mechanism reduces hand fatigue.
- Small, **lightweight design** provides greater accessibility.
- **Adjustable rear exhaust** directs air away from work piece.



Includes:

- 529 saw
- 3 fine tooth saw blades
- 3 coarse tooth saw blades,
- 8mm hex key
- Standard manuals

Accessories

- 6-pack 24T coarse blades — P4CS-6
- 6-pack 32T fine blades — P4FS-6



Specifications

Model	Strokes per Minute	Stroke Length in (mm)	Tool Weight lb (kg)	Tool Length in (mm)	Tool Width in (mm)	Tool Height in (mm)	Avg Air Consumption cfm (L/min)	Air Cons. @ Load cfm (L/min)	ISO15744		ISO28927		Rear Exhaust 360° Adjustable
									Sound Pressure / Power dBA	Air Inlet NPTF in	Min Hose Size in (mm)	Vibration Level (m/s ²) / K	
529	9500	3/8" (10)	1.5 (0.7)	9.7" (246)	1.9" (48)	2.6" (67)	1.1 (31)	1.13 (32)	84 / 95	1/4"	3/8" (10)	3.1 / 1.6	

Ingersoll Rand Industrial Technologies provides products, services, and solutions that enhance our customers' energy efficiency, productivity, and operations. Our diverse and innovative products range from complete compressed air systems, tools, and pumps to material and fluid handling systems. We also enhance productivity through solutions created by Club Car®, the global leader in golf and utility vehicles for businesses and individuals.

(800) 866-5457 · ingersollrandproducts.com/airsaw

